

Vestec 970 – Colour-Safe Hydrogen Peroxide

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation:Vestec 970Date of Safety Data Sheet:May 11, 2017Use of Preparation:Oxygen Bleach.

Company Identification: Parkside Professional Products Ltd.

4777 Kent Avenue

Niagara Falls, Ontario L2H 1J5 OFFICE: 905-358-8364

Company Emergency Telephone

Number

Transportation Emergency

Telephone Number

Emergency Phone: 905-358-8364

CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Emergency Overview:
OSHA / WHMIS 2015 Hazards
Classification of substance or mixture
GHS-US/Canadian classification:

Acute Toxicity Category 4 (Oral) - H302

Skin Irritation Category 2 - H315

Serious Eye Damage Category 1 - H318

Label Elements
GHS Labeling

Hazard Pictograms (GHS):



Signal Word (GHS): Danger Hazard Statements (GHS): H302: Harmful if swallowed. H315: Causes skin irritation.

H318: Causes serious eye damage. **Precautionary Statements (GHS)**:

P221: Take any precaution to avoid mixing with combustibles.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.



Vestec 970 – Colour-Safe Hydrogen Peroxide

Response Statements (GHS):

P301+P310+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Description:

Chemical

Ingredient	CAS#	% by Wt	Classification
Hydrogen Peroxide	7722-84-1	27-29	Acute Toxicity Category (Oral) 4 - H302 Skin Corrosion / Irritation Category 2 - H315 Serious Eye Damage / Eye Irritation Category 1- H318

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms persist consult physician.

Eye Contact: Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the

upper and lower eyelids. Get medical attention immediately.

Skin Contact: Thoroughly wash exposed skin with soap and water. Remove any contaminated

clothing and wash before reuse.

Ingestion: Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless

directed by medical personal. Never give anything to an unconscious person. Get

medical aid.

Notes to Physician: Treatment based on judgment of attending physician. Hydrogen peroxide at these

concentrations is a strong oxidant. Direct contact with the eye is likely to cause corneal damage especially if not washed immediately. Careful opthalmologic evaluation is recommended and the possibility of local corticosteroid therapy should be considered. Because of the likelihood of corrosive effects on the gastrointestinal tract after ingestion, and the unlikelihood of systemic effects, attempts at evacuating the stomach via emesis induction or gastric lavage should be avoided. There is a remote possibility, however, that a nasogastric or orogastric tube may be required for the reduction of severe distension due to gas formation.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Flood with water for extinguishing agent. CO2 may provide limited control.

Unsuitable extinguishing media: Do not use dry chemicals or foams.

Special exposure hazardsOxidizing substances can be decomposed by water and direct sources of heat.

Decomposition releases oxygen which can support combustion.



Vestec 970 - Colour-Safe Hydrogen Peroxide

Special safety equipment: Self-contained positive pressure breathing apparatus and protective clothing.

Fire and explosion Not flammable. Not an explosive hazard.

Further information Keep containers and surrounding cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures
General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

Information about fire - and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Protect from humidity and water.

Unsuitable material for receptacle: steel.

Unsuitable material for receptacle: aluminium.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Do not store together with alkaline products or strong acids or solvents.

Store away from reducing agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well-ventilated area.

Keep container tightly sealed.



Vestec 970 - Colour-Safe Hydrogen Peroxide

Specific end use(s) No further relevant information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Use local exhaust or dilution ventilation. If dust present use approved dust mask.

Hand protection: Chemical resistant gloves.

Eye protection: Safety goggles.

Skin protection: Use body-covering impervious clothing.

Working hygiene: Take usual precautions when handling. Workers should wash hands before

eating, drinking or smoking.

Exposure Guidelines:

Hydrogen Peroxide: British Columbia, Quebec, Ontario and Alberta

TWA: 1 ppm TWA: 1.4 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid
Α	\sim 1

Appearance Clear Odour Typical.

Colour Colourless. Odour Threshold No data available.

Property Values Remarks/Method

< 3.7 pН None known No data available Melting/Freezing Point None known **Boiling Point/Range** No data available None known Flash Point Not applicable. None known **Evaporation Rate** Similar None known Flammability (solid, gas) Not flammable None known

Flammability Limit in Air:

Upper LimitNo data availableNone knownLower LimitNo data availableNone knownVapour PressureNo data availableNone knownVapour densityNo data availableNone known

Specific Gravity 1.13 g/cm3

Water Solubility Soluble in water. None known Solubility Other Solvents No data available None known

Partition Coefficient:

n-octanol/waterNo data availableNone knownAutoignition temperatureNo data availableNone knownDecompositionNo data availableNone known

Temperature

Kinematic Viscosity No data available None known

Date: May 11, 2017



Vestec 970 - Colour-Safe Hydrogen Peroxide

Dynamic ViscosityNo data availableNone knownExplosive PropertiesNo data availableNone knownOxidizing PropertiesNo date availableNone known

Other Properties:

Softening Point

VOC Content %

Particle Size

Particle Size Distribution

No data available

No data available

No data available

10. STABILITY AND REACTIVITY

Reactivity Stable.

Chemical stability Stable under recommended handling and storage conditions (see section 7).

Thermal

decomposition/conditions to Self accelerating decomposition with oxygen release starting at 50 C.

avoid:

Possibility of hazardousContact with acids releases toxic gases.

reactions Reacts with alkali, metals and reducing agents.

Conditions to avoid

Store away from reducing agents, water, acids, bases salts of heavy metals,

organic materials, flammable substances wood sawdust.

Oxygen. Contamination with many substances will cause decomposition. The rate

Hazardous decomposition

eraduata

products

of decomposition increases with increasing temperature and may be very

vigorous with rapid generation of oxygen and steam at high temperatures of 50 C

or more.

Materials to avoid Warning! Do not use together with other products other than directed on the

product label.

Hazardous polymerization Will not occur

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

Hydrogen Peroxide CAS # 7722-84-1:

LD50 Oral Rat: 1200 mg/kg

LD50 Dermal Rabbit: Min 2000 mg/kg

Primary irritant effect:

on the skin: Caustic effect on mucous membranes. on the eye: Strong caustic or abrasive effect. Sensitization: No sensitizing effects known.

Additional toxicological information: The product shows the following dangers according to the calculation method:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of

esophagus and stomach.



Vestec 970 - Colour-Safe Hydrogen Peroxide

12. ECOLOGICAL INFORMATION

Toxicity: Not classified Persistence and Degradability: Not available Bioaccumulative Potential: Not available Mobility in Soil: Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international

regulations.

Ecology – Waste Materials: Avoid release to the environment.

14. TRANSPORTATION INFORMATION

Canadian T.D.G.: Regulated Material

Proper Shipping Name: Hydrogen Peroxide, Aqueous Solutions

Contains: N/A Hazard Class: 5.1 ID Number: UN 2984 Packing Group: II



U.S. Department of Transportation (DOT): Regulated material

Proper Shipping Name: Hydrogen Peroxide, Aqueous Solutions

Contains: N/A Hazard Class: 5.1 ID Number: UN 2984 Packing Group: II





Vestec 970 – Colour-Safe Hydrogen Peroxide

Water Transportation (IMDG): Regulated Material

Proper Shipping Name: Hydrogen Peroxide, Aqueous Solutions

Contains: N/A Hazard Class: 5.1 ID Number: UN 2984 Packing Group: II



Air Transportation (IATA): Regulated Material

Not permitted as containers are vented and vented containers are not permitted.

15. REGULATION

Occupational Health & Safety Regulations: WHMIS 1988 Classification: C, D1B, E



OSHA & WHMIS: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) and Canadian WHMIS regulations (Controlled Products Regulations under the Hazardous Products Act).

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies

KECL - PICCS -

AICS Complies



Vestec 970 – Colour-Safe Hydrogen Peroxide

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

EPA TSCA Inventory Appears.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

HMIS III Rating

Health: 3 Hazard

Flammability: 0 Minimal Hazard

Physical: 0 Minimal Hazard

Personal Protection: C

SDS US (GHS HazCom 2012 and WHMIS 2015)



Vestec 970 – Colour-Safe Hydrogen Peroxide

16. OTHER INFORMATION

Prepared By: Parkside Professional Products Ltd.

4777 Kent Avenue Niagara Falls, Ontario

L2H 1J5 905-358-8364

Issuing Date: May 11, 2017

Disclaimer:

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However, we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of Safety Data Sheet